

PRYSM®  
**SANKHYA-  
EP R201**  
SERVER  
DATA SHEET


## COMPUTING PERFORMANCE WITH HIGH MODULARITY

### Enrich your business with high performance and high modularity servers

Through innovative hardware design, software commonality and continued focus on system updates, PRYSM® Servers offers improved performance and pay-as-you-grow flexibility along with new features that help reduce the complexity involved in managing data for small, mid-sized and large enterprise business. These servers are designed to a PRYSM® - developed Behavioral Specification that defines consistent hardware layout and user interaction across all server models in this and future generations with cost optimized solution. These powerful systems are designed to meet the requirements of value segment in Small and Medium Enterprise, Business Intelligence IT, Data Analytics Storage and Cloud.

### Compute Performance - With Maximum Scalability, Operational & Networking Efficiency

Expand your possibilities with 2U systems based on the Sankhya- EP R201, the server product from PRYSM® family. This server family features power-efficient spread-core design, massive 24 DIMM DDR4 memory—up to 3.0 TB, PCIe Gen 3 lanes for the I/O and compute capacity needed to easily handle the intense needs of data analytics or enterprise applications. Designed to support the performance and features of Intel® Xeon® Scalable Processors, family up to 205W with 10-Gb Ethernet ports.



*In a rack-optimized 2U form factor, the PRYSM® delivers an excellent balance of outstanding performance, availability and flexibility for growing network infrastructure and high computing workload applications*

#### **SANKHYA- EP R201 IS AN EXCELLENT CHOICE FOR**

*Server with real time compute requirement*

*For hot and warm tier data and dense NVMe storage*

*Public and hybrid*

# Technical Specifications

FEATURES	PARAMETER	DESCRIPTION
Processor	Supported CPU Series	Intel® Xeon® Scalable Processor - Skylake - SP Series (Gold/Platinum)
	Thermal Design Power (TDP) wattage	Up to 205 W TDP
	Socket Type/Q'ty	Two Socket/Node - P LGA3647/(2)
	System Bus	UPI*3, PCIe Gen3 48 Lanes
Nodes	Nodes per Enclosure	1-4
Chipset	PCH	Intel® C628 Chipset
	Spec	PCIe 20 Lanes, USB3.0 *10\2.0*14, SATA3 * 14, 10 LAN*4, PCIe Uplink *16/*8, 26 W (SPEC:20W)
BMC	ASIC	AST2500A1-GP [ASPEED TECHNOLOGY INC.]
Memory	Max DIMM slots	2 DIMMs/CH, 6 CH/CPU, Total 24 DIMMs
	Max DIMM slots	DDR4 RDIMMs or LRDIMMs
	Memory Capacity	8/16/32/64/128 GB, Total 3072 GB
	Memory Speed	2666 MT/s for 1 DIMM/CH 2400 MT/s for 2 DIMM/CH
Expansion Slot (per NODE)	Memory Voltage	1.2V
	Ethernet	10 G *4 with X557-AT4 (Coppervale) 1G *1 for Management with RTL8211F
	PCIe 3.0	Riser 1 - PCIe 3.0 x 24 ; Riser 2 - PCIe 3.0 x 24; Riser 3 - PCIe 3.0 x 16
	Rear and Front IO	Rear IO : USB 3.0 x 2; RJ45 10G 4 Port *1, RJ45 Serial 1 Port *1, BMC RJ45 1G 1 Port *1; DB-15 *1
RAID Modules	VGA	(1) from BMC
	INTEL	RMSP3CD080F, RMSP3HD080E, RMS3JD160J,RSP3QD160J,RSPGD016J
Power Supply	Type	INTEL CPRS
	Redundancy	1+1
	Input Range	Full range AC (100 - 240 VAC)
	Output Watts	750 W, 1100W, 1300W
	Efficiency	DC 750W Gold, AC 1100W Platinum,AC Titanium
Chassis	Form Factor	1U Rack Mountable
	Storage	3.5" x 12 (up to 8x SAS+ 4 * NVMe/SAS) 2.5"x 24 (up to 20 x SAS +4 x NVMe/SAS)
	Dimensions	16.93" x 27.95" x 3.44"
BIOS	BRAND	AMI
	Feature	Hardware Monitor/SMBIOS 3.0/PnP/Wake on LAN/Boot from USB device/PXE via LAN/Storage/User Configurable FAN PWM Duty cycle/Console Redirection/ACPI Sleeping rate
System Cooling	FAN	6 hot swap system 60 x 60mm fans
Operating Environment	Operating Temp	10° C ~ 35° C (50° F ~ 95° F)
	Non Operating Temp	-40 ° C ~ 70 ° C (-40° F ~ 158° F)
	In/Non-Operating Humidity	25° C to 35° C
ROHS	RoHS 6/6 Complaint	Yes

## Contact Us:

Velankani Electronics Pvt. Ltd.  
43, Electronics City, Phase-1, Hosur Road, Bangalore- 560100, India  
Web: [www.velankanigroup.com](http://www.velankanigroup.com) | [www.prysmelectronics.com](http://www.prysmelectronics.com)  
Tel: +91- 80466 85850  
Mail: [insidesales@velankanigroup.com](mailto:insidesales@velankanigroup.com)



Quick Specs: [www.prysmelectronics.com/servers](http://www.prysmelectronics.com/servers)

Velankani Electronics Pvt. Ltd. (VEPL) is not responsible for errors in typography or photography. PRYSM, the PRYSM logo and PRYSM Server are trademarks of VEPL. Intel is a registered trademark and Xeon is a trademark of Intel Corporation. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. VEPL disclaims proprietary interest in the marks and names of others. © Copyright Velankani Electronics Pvt. Ltd. All rights reserved. Reproduction in any manner whatsoever without the express written permission of VEPL is strictly forbidden.